



2010 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145	55/115/175
Engine Oil/Oil Filter – change oil and replace filter	●	●	●
AdBlue Fluid – fill completely with fresh fluid (maximum capacity: 23 liters) and adapt learned values for AdBlue tank under guided fault finding after filling fluid	● Audi Q7 3.0L TDI only	● Audi Q7 3.0L TDI only	● Audi Q7 3.0L TDI only
Cooling System – check level, add if necessary		●	●
Engine On-Board Diagnostics – check fault memory		● A3, A6, S6, A8 only	● A3, A6, S6, A8 only
Engine Compartment – check for leaks		●	●
Battery – check and replace if necessary		●	●
Dust and Pollen Filter – replace		●	●
Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Thereafter, every 40,000 miles or 3 years, whichever occurs first. – replace at 55,000 miles or 6 years, whichever occurs first. Thereafter, every 60,000 miles or 6 years, whichever occurs first.		● S5K only; except A4, A5 and TTS with 2.0L TFSI engine	● A4, A5 and TTS with 2.0L TFSI engine only
Power Steering Fluid – check, add if necessary			●
Air Cleaner – clean housing, replace filter element		● S5K only; except Audi Q7 4.2L	● 75K only; Audi Q7 4.2L only
Ribbed V Belt and Tensioner – check condition and replace if necessary		● R8 only	● Audi Q7 3.6L, R8 only
Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary. – replace only the V belt for the compressor drive			● 75K only; V6 FSI, V6 TFSI (rear belt), 2.0L TFSI, 5.2L V10 FSI, 4.2L V8 FSI only ● 75K only; 3.0L TFSI only
Snow Screen for Air Cleaner – clean		● A4, S4, A5, S5 and A6 only	● A4, S4, A5, S5 and A6 only
Fuel Filter – remove water – replace		● Audi Q7 3.0L TDI only ● A3 2.0L TDI only	● Audi Q7 3.0L TDI and A3 2.0L TDI only
Diesel Particulate Filter (DPF) – check ash loading according to manufacturer’s work procedure, replace* if necessary.	● USA: 125K only; Audi Q7 3.0L TDI, A3 2.0L TDI only ● Canada: 200,000 km only; Audi Q7 3.0L TDI, A3 2.0L TDI only		
Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary		● except A3, Audi Q5	● except A3, Audi Q5
Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS) – check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS)	●	●	●
Tires – rotate, reset TPMS	● S5K only		
Wiper Blades – check condition and replace if necessary	●	●	●
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	●	●	●
Lights – check all lights, check headlight adjustment		● A8 only	● A3, A6, S6, A8 only
Lights – check all lights via instrument cluster. Check license plate light from the rear of the vehicle			● Audi Q7, A4, S4, Audi Q5, TT, A5, S5, R8 only
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			●
Doors – lubricate doors, check straps and hood latch		● A8 only	● Except A8
Rear Lid Hinges – lubricate		● A8 only	● A8 only
Service Reminder Display – reset	●	●	●
Horn – check function		●	●
Brake System – check for damage, leaks, pad thickness, fluid level	●	●	●
Brake Discs – check thickness			●
Exhaust System – check for damage, leaks		●	●
Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends		● A3, A6, S6, A8 only	●
Drive Shaft Boots – check		●	●
Automatic Transmission and Final Drive – check for leaks		●	●
Manual Transmission and Final Drive – check for leaks		●	●
Continuously Variable Transmission (multitronic) – change ATF			●
Haldex Clutch – change oil			● A3, TT only
DSG/S Tronic – change oil and replace filter element – change oil			● A3, TT only ● S4, S5 only
Underbody – check for damage and leaks		●	●
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock, power accessories and reset driver information display		●	●
Timing Belt – replace at 110K miles (175,000 km) on Audi TTS or 130K miles (205,000 km) on Audi A3 2.0L TDI only. Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary.			
Brake Fluid – replace every 2 years regardless of mileage.			
Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A5/S5 Cabriolet only).			

*If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (200,000 km), thereafter.

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.