## PROPANE-POWERED MICRO BIRD® G5 FORD - SCHOOL BUS





**COUNT ON BLUE BIRD** AS THE LEADER OF AFFORDABLE GREEN SOLUTIONS



## PROPANE-POWERED MICRO BIRD® G5 FORD - SPECIFICATIONS



	MODEL	200	200C	
BODY DIMENSIONS	Maximum passenger capacity	30	24	
	Number of rows	5	5	
	Exterior length overall	283"	283"	
	Exterior width overall	96"	96"	
Ē	Exterior height overall	113"	118"	
	Interior floor length	177.25"	177.25"	
Ξ	Interior width at hip	93"	93"	
	Interior height at center line	76"	76"	
<b>—</b>	Entrance door	32" x 80"	32" x 80"	
	Side windows	35" x 30"	35" x 30"	
	Rear bumper	3/16" x 9.5" with 12" wrap around		
	MODEL	200	200C	
	Wheelbase	158"	158"	
SIS	Engine	6.8 L	L gas omatic overdrive	
1SS	Transmission	5-speed auton		
丟	GVWR	14,500 lbs (6.8 L)		
FORD CHASSIS	Fuel tank	41 gallons		
	Brakes	4-wheel disc		
	Tires	LT225/75RX16E BSW all-season		
	Alternator	155 amp HD / 225 amp HD		
	Battery	72 amp HR 650 CCA		




- The Propane-Powered Micro Bird® uses Ford's E-450 chassis with 6.8L engine and ROUSH® propane system
- The horsepower and torque provides best in class performance
- Passenger capacity up to 30 passengers
- Also available with flat floor and wheelchair access door
- A 41 US gallon fuel tank allows the Propane-Powered Micro Bird® to travel up to 320 miles, depending on driving conditions
- Warranted by Ford and ROUSH®
- · Available exclusively at your local Blue Bird Dealer

STANDARD BODY EQUIPMENT	Bumper steel Emergency triangular warning device* Entrance door electric Entrance door grab handle left Floor steel Floor plywood 1/2" (4 ply) Flooring grey rib in aisle Flooring grey smooth under seat Flooring steps grey with white nosing FMVSS seat belt anchorage Heater 20,500 BTU Interior below window embossed aluminum Interior mirror 6" x 16" Joint strength Lift door (Model 200C only) Lights clearance LED Lights dome (4) Lights marker LED Lights stop and tail LED Lights turn LED	Mirrr Padd Pain Pain Pain Pain Pain Pain Reau Reau Reau Reflus Shub Shub Winu Winu Winu Winu Winu ** ** ** ** ** ** ** ** ** ** ** ** **
	Air conditioning Audio / P.A. systems Back-up sensors	Lift Ligh Ligh

rors crossview ors rearview ding all doors nt exterior yellow nt interior white nt roof white nt rub rail black ar door 2 windows ar door 3 point slide bar latch ar door retainer\* lective tape rear emergency exit\* of bow one piece, hat section type rail floor level rail seat level with wrap around it-off valve under body akers (2) pwell light LED lercoating dows back (2) tinted 62% dows rear door tinted 62% dows side tinted 62% andard in the US, optional in Canada wheelchair tie-down

Lift wheelchair tie-down
Lights back-up LED
Light monitoring system
Luggage containment systems
Reflective exterior signs
Remote / heated mirrors
Rub rail skirt level
Rub rail window level
Seats
Vandal lock system
Video monitoring / tracking system
Wheelchair and occupant restraint system
Wheelchair lift with interlock device



DISTRIBUTED BY:

More options available: Specifications shown in this brochure were in effect at time of printing. In keeping with its policy of continual improvement, Micro Bird, Inc. reserves the right to change specifications without notice and without incurring obligations.





Barriers

Bumper aluminum

Driver side auxiliary step

Entrance door grab handle right Floor plywood 5/8" (5 ply) marine grade

Lap and shoulder belt seating

Lift door with tinted windows

Emergency equipment

Heater 42,000 BTU

Lift wheelchair

Integrated toddler seats

Electronic sleeping child monitoring system