

2020 RAM - Promaster City - Trailer Towing Chart - SAE J2807 compliant												
Engine	Transmission	Mkt	Axle Ratio	GVWR	Payload ¹	Base Weight			GAWR			
						Total	Front	Rear	Front	Rear	GCWR ²	Max. Trailer Weight Rating ³
RAM Promaster City												
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	USA	3.73	5,395	1,890	3,501	2,206	1,295	2,690	2,866	5,900	2,000
2.4L I4 GASOLINE MULTIAIR ENGINE	9-SPD AUTO 948TE - DFH	CAN	3.73	5,395	1,900	3,497	2,210	1,287	2,690	2,866	5,900	2,000

- 1. Payload and Max Trailer weights are ESTIMATED values.
- 2. All values are shown in pounds unless otherwise stated
- 3. (1) Payload is rounded to the nearest 10 lb (Payload = GVWR Base Weight)
- 4. (2) GCWR is a defined value from Vehicle Engineering in lbs (max GCWR = 5,900 lbs)
- 5. (3) Max Trailer weight is limited to 2,000 lbs.
- 6. Payload and Maximum Trailer weight are mutually exclusive.
- 7. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807.
 - Driver and passenger Weight = 300 lb.
 - Trailering Equipment Weight: 50.7 lb for Conventional Hitch.
- 8 . The recommended tongue weight is 10% of trailer weight.
- 9. Hitch rating, GVWR, GAWRs, and GCWR should never be exceeded.