

## S P E C I F I C A T I O N   P R O P O S A L

Description	Weight Front	Weight Rear
<b>➤ Vehicle Configuration</b>		
➤ 4700 SET-FORWARD FRONT AXLE CHASSIS	9,100	6,720
➤ 2017 MODEL YEAR SPECIFIED		
➤ SET FORWARD AXLE - TRACTOR	40	
➤ LH PRIMARY STEERING LOCATION		
<b>➤ General Service</b>		
➤ TRACTOR/TRAILER CONFIGURATION		
➤ DOMICILED, CANADA (OTHER THAN QUEBEC)		
➤ PICKUP AND DELIVERY/SHORT HAUL SERVICE		
➤ TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
➤ MAXIMUM 8% EXPECTED GRADE		
➤ SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
➤ WESTERN STAR ON-HIGHWAY WARRANTY		
➤ EXPECTED FRONT AXLE(S) LOAD : 12000.0 lbs		
➤ EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs		
➤ EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 52000.0 lbs		
➤ EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs		
<b>➤ Tractor Service</b>		
➤ SINGLE (1) TRAILER		
<b>➤ Engine</b>		
➤ DETROIT DD13 12.8L 410 HP @ 1625 RPM, 1900 GOV RPM, 1450 LB/FT @ 975 RPM		
<b>➤ Electronic Parameters</b>		
➤ 65 MPH ROAD SPEED LIMIT		
➤ CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT		
➤ PTO MODE ENGINE RPM LIMIT - 900 RPM		
➤ PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED OR PARK BRAKE NOT APPLIED		
➤ PTO MODE CLUTCH OVERRIDE - CLUTCH ENABLED		
➤ PTO RPM WITH CRUISE SET SWITCH - 600 RPM		
➤ PTO RPM WITH CRUISE RESUME SWITCH - 600 RPM		
➤ PTO MODE CANCEL VEHICLE SPEED - 5 MPH		
➤ PTO MODE RPM INCREMENT - 25 RPM		
➤ PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND		

HY4064



Description	Weight Front	Weight Rear
<ul style="list-style-type: none"> <li>➤ ONE REMOTE PTO SPEED</li> <li>➤ REMOTE PTO SPEED 1 SETTING - 900 RPM</li> <li>➤ SOFT CRUISE CONTROL ENABLED</li> <li>➤ PTO MINIMUM RPM - 600</li> <li>➤ ENABLE AUTO ENGINE RPM ELEVATE FOR EXTENDED IDLE</li> </ul>		
<b>➤ Engine Equipment</b>		
<ul style="list-style-type: none"> <li>➤ 2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION</li> <li>➤ VEHICLE IS SUBJECT TO EPA GHG14/GHG17, DOES NOT HAVE REGULATORY VEHICLE SPEED LIMITER (VSL) OR AUTOMATIC ENGINE SHUTDOWN(AES)</li> <li>➤ 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)</li> <li>➤ STANDARD OIL PAN</li> <li>➤ ENGINE MOUNTED OIL CHECK AND FILL</li> <li>➤ ONE PIECE VALVE COVER</li> <li>➤ SIDE OF HOOD AIR INTAKE WITH DONALDSON HIGH CAPACITY AIR CLEANER WITH SAFETY ELEMENT, FIREWALL MOUNTED</li> <li>➤ DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE</li> <li>➤ (3) ALLIANCE ABSORBED GLASS MAT MODEL 7A31, GROUP 31, 12 VOLT MAINTENANCE FREE 2190 CCA THREADED STUD BATTERIES</li> <li>➤ PASSENGER SEAT BATTERY BOX VENTED TO OUTSIDE OF CAB</li> <li>➤ BATTERY BOX MOUNTED UNDER PASSENGER SEAT</li> <li>➤ WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN</li> <li>➤ PLASTIC BATTERY BOX COVER</li> <li>➤ EATON EASY PEDAL ADVANTAGE 15-1/2 INCH MANUALLY ADJUSTED CLUTCH</li> <li>➤ TORQUE LIMITING CLUTCH BRAKE</li> <li>➤ ZERK FITTING WITH EXTENSION HOSE AT CLUTCH RELEASE BEARING</li> <li>➤ MECHANICAL CLUTCH CONTROL</li> <li>➤ BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE</li> <li>➤ ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM</li> <li>➤ JACOBS COMPRESSION BRAKE</li> <li>➤ RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE</li> </ul>		



Description	Weight Front	Weight Rear
➤ ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
➤ 12 FOOT 06 INCH (150 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
➤ RH CURVED VERTICAL TAILPIPE B-PILLAR MOUNTED ROUTED FROM STEP		
➤ 13 GALLON DIESEL EXHAUST FLUID TANK	35	10
➤ LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION		
➤ STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD		
➤ BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH		
➤ AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED		
➤ DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR		
➤ FULL FLOW OIL FILTER		
➤ 1500 SQUARE INCH ALUMINUM RADIATOR		
➤ ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT		
➤ GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
➤ CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
➤ HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE		
➤ NO RADIATOR/OIL PAN GUARD	-5	
➤ PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER		
➤ PHILLIPS-TEMRO 300 WATT/115 VOLT OIL PREHEATER		
➤ CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
➤ ALUMINUM FLYWHEEL HOUSING		
➤ DELCO 12V MOD 3.175-39MT+ OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH		

➤ **Transmission**

➤ <b>EATON FULLER RTLO-16913A TRANSMISSION</b>	90	40
--	----	----

➤ **Transmission Equipment**

➤ CAST IRON CLUTCH HOUSING		
➤ MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION FILL AND DRAIN, AXLE(S) FILL AND DRAIN		
➤ PAINTED SHIFT LEVER, SOLID LINKAGE		
➤ WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		

HY4064



Description	Weight Front	Weight Rear
➤ SYNTHETIC TRANSMISSION LUBE		
<b>➤ Front Axle and Equipment</b>		
➤ DETROIT DA-F-12.0-3 12,000# FF1 71.5 KPI/3.74 DROP SINGLE FRONT AXLE	-190	
➤ MERITOR 16.5X5 Q+ STAMPED SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, PLATINUM SHIELD SHOES	-10	
➤ CONMET CAST IRON FRONT BRAKE DRUMS		
➤ FRONT BRAKE DUST SHIELDS	5	
➤ WABCO LONGSTROKE FRONT BRAKE CHAMBERS		
➤ HALDEX AUTOMATIC FRONT SLACK ADJUSTERS		
➤ TRW THP-60 POWER STEERING	-40	
➤ 2 QUART SEE THROUGH POWER STEERING RESERVOIR		
➤ SYNTHETIC 50W FRONT AXLE LUBE		
<b>➤ Front Suspension</b>		
➤ 12,000# DUAL TAPERLEAF FRONT SUSPENSION	-188	
➤ MAINTENANCE FREE RUBBER BUSHINGS - FRONT SUSPENSION		
➤ FRONT SHOCK ABSORBERS		
<b>➤ Rear Axle and Equipment</b>		
➤ DETROIT DA-RT-40.0-4 HT 40,000# R-SERIES TANDEM REAR AXLE		
➤ 3.58 REAR AXLE RATIO		
➤ MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES		
➤ MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES		
➤ (1) INTERAXLE LOCK VALVE FOR TANDEM OR TRIDEM DRIVE AXLES		
➤ INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH		
➤ MERITOR 16.5X8.62 Q+ STAMPED SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, PLATINUM SHIELD SHOES		
➤ 2011/2013-FMVSS 121 REAR BRAKE LININGS		
➤ BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
➤ CONMET CAST IRON REAR BRAKE DRUMS		
➤ REAR BRAKE DUST SHIELDS		10
➤ HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		
➤ HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
➤ SYNTHETIC 75W-90 REAR AXLE LUBE		
<b>➤ Rear Suspension</b>		

Description	Weight Front	Weight Rear
➤ AIRLINER 40,000# REAR SUSPENSION		-70
➤ AIRLINER HIGH POSITION RIDE HEIGHT		
➤ 51 INCH AXLE SPACING		
➤ MANUAL DUMP VALVE FOR AIR SUSPENSION WITH GAUGE		
➤ INDICATOR LIGHT FOR EACH REAR SUSPENSION CONTROL SWITCH		
➤ SINGLE AIR REAR SUSPENSION LEVELING VALVE		
➤ TRANSVERSE CONTROL RODS		
➤ REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)		

### ➤ Brake System

- WABCO 4S/4M ABS WITHOUT TRACTION CONTROL
- REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
- FIBER BRAID PARKING BRAKE HOSE
- WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER
- WABCO OIL COALESCING FILTER FOR AIR DRYER
- AIR DRYER MOUNTED OUTBOARD ON LH RAIL
- STEEL AIR BRAKE RESERVOIRS
- PULL CABLES ON ALL AIR RESERVOIR(S)

### ➤ Trailer Connections

- |  |    |
|--|----|
| ➤ 12 FOOT STRAIGHT TRAILER AIR HOSE  | 10 |
| ➤ 49.5 INCH STAINLESS STEEL SLIDE BAR WITH SPRING TYPE AIR HOSE HANGER                               | 2  |
| ➤ COMBINATION DUMMY GLAD HANDS AND LIGHT PLUG HOLDER   |    |
| ➤ PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION |    |
| ➤ SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE FRAME MOUNTED AFT CAB                              |    |
| ➤ 12 FOOT DETACHABLE STRAIGHT PRIMARY TRAILER ELECTRICAL CABLE WITH SAE J560 CONNECTOR               | 10 |

### ➤ Wheelbase & Frame

- 4575MM (180 INCH) WHEELBASE
- 11/32X3-1/2X10-15/16 INCH STEEL FRAME (8.73MMX277.8MM/0.344X10.94 INCH) 120KSI
- 1600MM (63 INCH) REAR FRAME OVERHANG
- CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 98.78 in
- CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 94.78 in
- FLANGED TAPERED END OF FRAME

HY4064



Description	Weight Front	Weight Rear
<b>➤ Chassis Equipment</b>		
➤ LH BACK OF CAB ACCESS, GRAB HANDLES WITH SINGLE RUBBER INSERT	5	5
➤ 21 INCH (525MM) DECK PLATE FLUSH MOUNTED BETWEEN RAILS	8	7
➤ 18 INCH CHROMED STEEL BUMPER	20	
➤ REMOVABLE FRONT TOW HOOKS STORED ON THE CHASSIS FRAME	25	
➤ BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
➤ NU-LINE STAINLESS STEEL MUDFLAP BRACKETS		25
➤ WESTERN STAR LOGO BLACK MUDFLAPS		15
➤ FRONT ANTI-SPRAY CAB MOUNTED MUDFLAPS		
➤ GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
➤ STAINLESS STEEL QUARTER FENDERS WITH LOGO		30
<b>➤ Fifth Wheel</b>		
➤ JOST JSK37 SERIES 24.0 INCH AIR SLIDE FIFTH WHEEL - 2 INCH SLIDE INCREMENTS	30	510
➤ FIFTH WHEEL 406MM (16.0 INCHES) AHEAD OF SUSPENSION CENTERLINE		
➤ 197MM (7.75 INCH) FIFTH WHEEL HEIGHT		
➤ OUTBOARD ANGLE - FIFTH WHEEL MOUNTING		
➤ DASH MOUNTED CONTROL VALVE AND PLUMBING FOR FIFTH WHEEL		
➤ LH FIFTH WHEEL RELEASE		
<b>➤ Fuel Tanks</b>		
➤ 100 GALLON/378 LITER ALUMINUM FUEL TANK - LH	20	
➤ 25 INCH DIAMETER FUEL TANK(S)		
➤ PLAIN ALUMINU FUEL TANK(S) WITH POLISHED STAINLESS STEEL BANDS		
➤ FUEL TANK(S) FORWARD		
<b>➤ Tires</b>		
➤ CONTINENTAL HSL2 11R22.5 14 PLY RADIAL FRONT TIRES	8	
➤ CONTINENTAL HD3 ECO PLUS 11R22.5 14 PLY RADIAL REAR TIRES		152
<b>➤ Hubs</b>		
➤ CONMET PRESET PLUS IRON FRONT HUBS		
➤ CONMET PRESET PLUS IRON REAR HUBS		
<b>➤ Wheels</b>		
➤ ACCURIDE 41644 ACCU-LITE 22.5X8.25 10-HUB PILOT 5.72 INSET ALUMINUM DISC FRONT WHEELS	-50	

HY4064



Description	Weight Front	Weight Rear
➤ ACCURIDE 41644 ACCU-LITE 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-200
➤ NYLON WHEEL GUARDS FRONT AND REAR ALL INTERFACES		
<b>➤ Cab Exterior</b>		
➤ 110 INCH BBC STEEL CONVENTIONAL CAB		
➤ WESTERN STAR STAINLESS STEEL CAB SKIRT		
➤ AIR CAB MOUNTS WITH CHECK VALVE		
➤ STAINLESS STEEL SILL PLATES	5	
➤ NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		
➤ LH AND RH EXTERIOR GRAB HANDLES WITH RUBBER INSERTS AND RH INTERIOR GRAB HANDLE MOUNTED TO A POST		
➤ STATIONARY BRIGHT FINISH GRILLE		
➤ CHROME HOOD MOUNTED AIR INTAKE GRILLE		
➤ HEAVY DUTY STEEL CAB FLOOR		
➤ FIBERGLASS HOOD		
➤ WESTERN STAR NAMEPLATES		
➤ DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS		
➤ SINGLE ELECTRIC HORN		
➤ DUAL HORN SHIELDS		
➤ DOORS AND IGNITION KEYED THE SAME		
➤ REAR LICENSE PLATE MOUNT END OF FRAME		
➤ SINGLE RECTANGULAR SEALED BEAM HEADLIGHTS WITH BRIGHT BEZELS		
➤ (5) AMBER MARKER LIGHTS		
➤ DAYTIME RUNNING LIGHTS		
➤ INTEGRAL STOP/TAIL/BACKUP LIGHTS		
➤ STANDARD FRONT TURN SIGNAL LAMPS		
➤ (2) FLUSH UTILITY LIGHTS MOUNTED BACK OF CAB/SLEEPER	6	
➤ DUAL STAINLESS STEEL HEATED MIRRORS		
➤ DOOR MOUNTED MIRRORS		
➤ 102 INCH EQUIPMENT WIDTH		
➤ LH AND RH 8 INCH STAINLESS STEEL CONVEX MIRRORS MOUNTED BELOW PRIMARY MIRRORS		
➤ RH DOWN VIEW MIRROR		
➤ RH AFTERTREATMENT SYSTEM CAB ACCESS WITH PLAIN DIAMOND PLATE COVER		
➤ STAINLESS STEEL EXTERIOR SUN VISOR	28	
➤ 17.5X35 INCH TINTED REAR WINDOW		
➤ TINTED DOOR GLASS		
➤ MANUAL DOOR WINDOW REGULATORS		

HY4064



	Description	Weight Front	Weight Rear
➤	2-PIECE TINTED CURVED BONDED WINDSHIELD		
➤	2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, MOUNTED UNDER CAB, WITH REMOTE FILL		
<b>➤ Cab Interior</b>			
➤	GRAY VINYL BASE INTERIOR		
➤	BLACK HARD TRIM		
➤	BASE LEFT HAND DOOR TRIM		
➤	BASE RIGHT HAND DOOR TRIM		
➤	BLACK MATS WITH DOUBLE INSULATION		
➤	DASH MOUNTED ASH TRAY AND LIGHTER, DRIVER SIDE		
➤	FORWARD ROOF MOUNTED CONSOLE		
➤	PASSENGER SIDE WING DASH MOUNTED GLOVE BOX WITH LOCKING DOOR		
➤	LH AND RH DOOR MAP POCKETS		
➤	COAT HOOK ON RH BACKWALL OF CAB		
➤	(1) CUP HOLDER MOUNTED IN BOTTOM CENTER OF DASH		
➤	TWO-TONE CHARCOAL UPPER/COOL GRAY LOWER SOFT TOUCH WING DASH WITH BLACK DRIVER SIDE COSMETIC UNDER DASH COVER		
➤	STANDARD WIRING		
➤	2-1/2 LB. FIRE EXTINGUISHER MOUNTED OUTBOARD OF DRIVER SEAT	5	
➤	HEATER, DEFROSTER AND AIR CONDITIONER WITH CONSTANT OUTLET TEMPERATURE CONTROL		
➤	HVAC DUCTING WITH FOAM MAIN FRESH AIR FILTER AND OUTSIDE PRE-FILTER		
➤	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
➤	CAB INSULATION		
➤	CIRCUIT FUSES		
➤	DOOR ACTIVATED DOME LIGHT, UNDER DASH LIGHT AND LH AND RH DOOR MOUNTED COURTESY LIGHTS		
➤	CAB DOOR LATCHES WITH MANUAL DOOR LOCKS		
➤	TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10	
➤	BASIC HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION AND REAR CUSHION TILT		
➤	BATTERY BOX MID BACK NON SUSPENSION PASSENGER SEAT		
➤	INBOARD DRIVER SEAT ARMREST, NO PASSENGER SEAT ARMREST	2	
➤	MORDURA CLOTH DRIVER SEAT		
➤	MORDURA CLOTH PASSENGER SEAT		
➤	3 POINT DRIVER AND PASSENGER SEAT BELT RETRACTORS		

HY4064





Description	Weight Front	Weight Rear
➤ ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
➤ 2-SPOKE 18 INCH (450MM) BLACK STEERING WHEEL(S)		
➤ DRIVER AND PASSENGER INTERIOR SUN VISORS		
<b>➤ Instruments &amp; Controls</b>		
➤ ELECTRONIC ACCELERATOR CONTROL		
➤ STAR GAUGES WITH BRIGHT BEZELS		
➤ ROYAL ROSEWOOD MATTE FINISH DRIVER INSTRUMENT PANEL		
➤ ROSEWOOD VINYL MATTE FINISH CENTER INSTRUMENT PANEL INSERT		
➤ LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM		
➤ 2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES		
➤ INTAKE MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS		
➤ 97 DB BACKUP ALARM		3
➤ CRUISE CONTROL SWITCHES IN THE CENTER PANEL		
➤ KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
➤ WARNING LAMP/LIGHT BAR DISPLAY, NON-DATA LINKED		
➤ HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		
➤ 2 INCH ELECTRIC FUEL GAUGE		
➤ FUEL FILTER RESTRICTION INDICATOR		
➤ EMISSIONS LIMITED IDLE ADJUST		
➤ ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
➤ 2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
➤ ELECTRIC ENGINE OIL PRESSURE GAUGE		
➤ AM/FM/WB RADIO WITH CD PLAYER, BLUETOOTH AND MICROPHONE, USB, FRONT AND REAR AUXILIARY INPUTS AND J1939	10	
➤ ROOF/OVERHEAD CONSOLE MOUNTED RADIO		
➤ (4) RADIO SPEAKERS IN CAB		
➤ COBRA 29 WX ST FACTORY INSTALLED CB RADIO WITH WEATHERBAND	5	
➤ MULTI-BAND AM/FM/WB/CB DUAL MIRROR MOUNTED ANTENNA SYSTEM	4	
➤ ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITH ODOMETER		
➤ ELECTRONIC 3000 RPM TACHOMETER		
➤ DETROIT CONNECT VIRTUAL TECHNICIAN CONNECTIVITY PACKAGE (DETROIT ENGINES ONLY)		
➤ 5 YEARS TOTAL VIRTUAL TECHNICIAN REMOTE DIAGNOSTICS SERVICE (3 YEARS ADDITIONAL TO STANDARD)		

HY4064



	Description	Weight Front	Weight Rear
➤	BW TRACTOR PROTECTION VALVE		
➤	TRAILER HAND CONTROL BRAKE VALVE		
➤	2 INCH VOLTMETER		
➤	SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
➤	CAB/TRAILER MARKER LIGHT SWITCH WITH SEPARATE HEADLIGHT SWITCH AND INTERRUPT SWITCH FOR TRAILER MARKER LIGHTS		
➤	TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
➤	VSM NON CANCELING TURN SIGNAL SWITCH WITH INTEGRAL HEADLAMP DIMMER WITHOUT BRAKE OVERRIDE		
➤	PACIFIC INSIGHT ELECTRONIC FLASHER		
<b>➤ Design</b>			
➤	PAINT: ONE SOLID COLOR		
<b>➤ Color</b>			
➤	CAB COLOR A: HSB915662 BLUE DIAMOND MET PPG BASE/CLEAR		
➤	CAB INTERIOR PAINTED SAME AS CAB COLOR		
➤	BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT		

**T O T A L V E H I C L E S U M M A R Y**

**Weight Summary**

	Weight Front	Weight Rear	Total Weight
Factory Weight <sup>+</sup>	8990 lbs	7267 lbs	16257 lbs
Total Weight <sup>+</sup>	8990 lbs	7267 lbs	16257 lbs

**Extended Warranty**

- EW4 DD13 VOC \$0 DEDUCTIBLE 7 YEAR/250000 MILES FULL COVERAGE

(+) Weights shown are estimates only.  
 If weight is critical, contact Customer Application Engineering.

