

S P E C I F I C A T I O N P R O P O S A L

Description	Weight Front	Weight Rear
➤ Vehicle Configuration		
➤ WESTERN STAR 4900SA CHASSIS	9,674	6,846
➤ 2018 MODEL YEAR SPECIFIED		
➤ SET BACK AXLE - TRUCK	-10	
➤ TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK	10	10
➤ LH PRIMARY STEERING LOCATION		
➤ General Service		
➤ TRUCK/TRAILER CONFIGURATION		
➤ DOMICILED, CANADA (OTHER THAN QUEBEC)		
➤ CONSTRUCTION SERVICE		
➤ DIRT/SAND/ROCK COMMODITY		
➤ TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
➤ MAXIMUM 8% EXPECTED GRADE		
➤ SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
➤ WESTERN STAR VOCATIONAL WARRANTY		
➤ EXPECTED FRONT AXLE(S) LOAD : 20000.0 lbs		
➤ EXPECTED REAR DRIVE AXLE(S) LOAD : 40000.0 lbs		
➤ EXPECTED PUSHER AXLE(S) LOAD : 20000.0 lbs		
➤ EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 80000.0 lbs		
➤ EXPECTED GROSS COMBINATION WEIGHT : 110000.0 lbs		
➤ Tractor Service		
➤ SINGLE (1) TRAILER		
➤ Engine		
➤ DETROIT DD15 14.8L 505 HP @ 1625 RPM, 1900 GOV RPM, 1750 LB/FT @ 975 RPM		
➤ Electronic Parameters		
➤ 65 MPH ROAD SPEED LIMIT		
➤ CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT		
➤ PTO MODE ENGINE RPM LIMIT - 900 RPM		
➤ PTO MODE BRAKE OVERRIDE - SERVICE BRAKE APPLIED OR PARK BRAKE NOT APPLIED		
➤ PTO MODE CLUTCH OVERRIDE - CLUTCH ENABLED		
➤ PTO RPM WITH CRUISE SET SWITCH - 600 RPM		
➤ PTO RPM WITH CRUISE RESUME SWITCH - 600 RPM		
➤ ENABLE REGENERATION IN PTO MODE		
➤ ONE REMOTE PTO SPEED		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ REMOTE PTO SPEED 1 SETTING - 900 RPM		
➤ SOFT CRUISE CONTROL ENABLED		
➤ PTO MINIMUM RPM - 600		
➤ ENABLE DPF REGEN ZONE 1		
➤ Engine Equipment		
➤ 2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/FINAL GHG17 CONFIGURATION		
➤ 2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)		
➤ DUAL POLISHED STAINLESS STEEL 13 INCH DONALDSON COWL MOUNTED 1-STAGE AIR CLEANERS WITH POLISHED STAINLESS STEEL BANDS	40	
➤ DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE		
➤ (4) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 4400 CCA THREADED STUD BATTERIES	50	10
➤ STACK BATTERY BOX		
➤ SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
➤ WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
➤ NON-POLISHED BATTERY BOX COVER		
➤ EATON EASY PEDAL ADVANTAGE 15-1/2 INCH MANUALLY ADJUSTED CLUTCH		
➤ TORQUE LIMITING CLUTCH BRAKE		
➤ ZERK FITTINGS WITH EXTENSION HOSES AT CLUTCH RELEASE BEARING AND X-SHAFT		
➤ BW MODEL BA-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE		
➤ ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM		
➤ JACOBS COMPRESSION BRAKE		
➤ RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH DUAL CAB MOUNTED VERTICAL TAILPIPES	55	33
➤ ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
➤ 12 FOOT 06 INCH (150 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT		
➤ STANDARD CURVE BRIGHT UPPER STACK(S) AND ELBOW(S)		
➤ DUAL CURVED VERTICAL TAILPIPES B-PILLAR MOUNTED		
➤ 23 GALLON DIESEL EXHAUST FLUID TANK		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ NON-POLISHED ALUMINUM DIESEL EXHAUST FLUID TANK COVER		
➤ STANDARD DIESEL EXHAUST FLUID TANK CAP		
➤ OVAL PERFORATED DUAL STAINLESS STEEL MUFFLER/TAIPIPE SHIELDS WITH WESTERN STAR LOGO		
➤ BORG WARNER (KYSOR) REAR AIR ON/OFF ENGINE FAN CLUTCH		
➤ AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED		
➤ DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR		
➤ FULL FLOW OIL FILTER		
➤ 1500 SQUARE INCH ALUMINUM RADIATOR	-130	
➤ ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT		
➤ GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		
➤ CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
➤ HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE		
➤ PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4	
➤ CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR		
➤ DELCO 12V MOD 3.175-39MT+ OCP STARTER WITH THERMAL PROTECTION AND INTEGRATED MAGNETIC SWITCH		
➤ CAST IRON FRONT AND REAR ENGINE SUPPORTS		
➤ Transmission		
➤ EATON FULLER RTLO-18918B TRANSMISSION	90	40
➤ Transmission Equipment		
➤ VEHICLE INTERFACE WIRING WITH BODY BUILDER BLUNT CUT WIRE INTERFACE AT BACK OF CAB		
➤ CAST IRON CLUTCH HOUSING		
➤ PTO MOUNTING, RH SIDE OF MAIN TRANSMISSION		
➤ PAINTED SHIFT LEVER, SOLID LINKAGE		
➤ WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
➤ SYNTHETIC TRANSMISSION LUBE		
➤ Front Axle and Equipment		
➤ MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE	150	
➤ MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	20	
➤ NON-ASBESTOS FRONT BRAKE LINING		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ CONMET CAST IRON FRONT BRAKE DRUMS		
➤ FRONT BRAKE DUST SHIELDS	5	
➤ MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
➤ TRW THP-60 POWER STEERING WITH RCH45 AUXILIARY GEAR	130	
➤ 4 QUART POWER STEERING RESERVOIR		
➤ OIL/AIR POWER STEERING COOLER		
➤ SYNTHETIC 75W-90 FRONT AXLE LUBE		
➤ Front Suspension		
➤ 20,000# FLAT LEAF FRONT SUSPENSION	305	
➤ THREADED SPRING PINS AND BUSHINGS - FRONT SUSPENSION		
➤ ALUMINUM SPACER BLOCKS FOR FRONT SUSPENSIONS		
➤ FRONT SHOCK ABSORBERS		
➤ Rear Axle and Equipment		
➤ RT-46-160 46,000# R-SERIES TANDEM REAR AXLE		420
➤ 3.91 REAR AXLE RATIO		
➤ MXL 18N MERITOR EXTENDED LUBE MAIN DRIVELINE WITH FULL ROUND YOKES	80	80
➤ MXL 17N MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH FULL ROUND YOKES		
➤ DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		40
➤ (1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE		
➤ INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH		
➤ INDICATOR LIGHT FOR EACH DRIVER CONTROLLED TRACTION DEVICE SWITCH		
➤ MERITOR 16.5X8.62 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
➤ NON-ASBESTOS REAR BRAKE LINING		
➤ BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS		
➤ CONMET CAST IRON REAR BRAKE DRUMS		
➤ REAR BRAKE DUST SHIELDS		10
➤ HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS		
➤ MERITOR AUTOMATIC REAR SLACK ADJUSTERS		
➤ SYNTHETIC 75W-90 REAR AXLE LUBE		
➤ Rear Suspension		
➤ AIRLINER 46,000# REAR SUSPENSION		480

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ AIRLINER HIGH POSITION RIDE HEIGHT		
➤ WELDED AXLE SEATS SUPPLIED ON REAR AXLE		
➤ 51 INCH AXLE SPACING		
➤ MANUAL DUMP VALVE FOR AIR SUSPENSION WITH INDICATOR LIGHT AND GAUGE		
➤ SINGLE AIR REAR SUSPENSION LEVELING VALVE		
➤ TRANSVERSE CONTROL RODS		
➤ REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)		
➤ Pusher / Tag Equipment		
➤ HENDRICKSON SC20 COMPOSILITE 20,000# AIR LIFT STEERABLE PUSHER SUSPENSION, 16.5X6 BRAKES AND FL1 AXLE	925	925
➤ HENDRICKSON SC20/SCO20 20,000# FL1 STEERABLE 16.5X6 BRAKE INTEGRAL PUSHER AXLE		
➤ HENDRICKSON 16.5X6 CAST SPIDER CAM PUSHER/TAG BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		
➤ CONMET CAST IRON PUSHER/TAG BRAKE DRUMS		
➤ PUSHER/TAG BRAKE DUST SHIELDS		5
➤ HALDEX LONGSTROKE PUSHER/TAG AXLE SERVICE CHAMBERS		
➤ HALDEX AUTOMATIC PUSHER/TAG SLACK ADJUSTERS		
➤ HENDRICKSON SC20 COMPOSILITE 20,000# STEERABLE AIR LIFT PUSHER SUSPENSION		
➤ 101 INCH AXLE SPACING PUSHER/TAG		
➤ Brake System		
➤ WABCO 4S/4M ABS WITHOUT TRACTION CONTROL		
➤ REINFORCED NYLON AIR LINES		
➤ FIBER BRAID PARKING BRAKE HOSE		
➤ STANDARD BRAKE SYSTEM VALVES		
➤ COMBO-ABS/SERVICE BRAKE VALVE WITH 5.5 PSI CRACK PRESSURE		
➤ BW AD-9 BRAKE LINE AIR DRYER WITH HEATER	20	
➤ AIR DRYER MOUNTED INBOARD ON LH RAIL		
➤ STEEL AIR BRAKE RESERVOIRS		
➤ PULL CABLES ON ALL AIR RESERVOIR(S)		
➤ Trailer Connections		
➤ AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS	5	5
➤ PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME		
➤ Wheelbase & Frame		
➤ 6750MM (266 INCH) WHEELBASE		
➤ 3/8X3-7/8X11-5/8 INCH DOUBLE CHANNEL 120KSI STEEL FRAME (3/8 INCH OUTER AND 1/4 INCH INNER)	1,070	670
➤ 2800MM (110 INCH) REAR FRAME OVERHANG		
➤ CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 193.0 in		
➤ CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 187.28 in		
➤ UNDERSLUNG CROSSMEMBER	40	
➤ SQUARE END OF FRAME		
➤ FRONT CLOSING CROSSMEMBER		
➤ EXTRA HEAVY DUTY STEEL C-CHANNEL BOLTED CONSTRUCTION BACK OF TRANSMISSION CROSSMEMBER		
➤ EXTRA HEAVY DUTY STEEL C-CHANNEL BOLTED CONSTRUCTION MIDSHIP #1 CROSSMEMBER	5	5
➤ 1/4 INCH STEEL C-CHANNEL CROSSMEMBER WITHOUT A-FRAME, NON-TOWING		50
➤ HEAVY DUTY SUSPENSION CROSSMEMBER		30
➤ EXTRA HEAVY DUTY STEEL C-CHANNEL BOLTED CONSTRUCTION REAR MOUNTED SUSPENSION CROSSMEMBER		
➤ Chassis Equipment		
➤ 14 INCH TAPERED SWEPTBACK CHROMED STEEL BUMPER		
➤ NON REMOVABLE CENTERED FRONT TOW PIN FOR HIGHWAY OR CONSTRUCTION BUMPER		
➤ BUMPER MOUNTING FOR SINGLE LICENSE PLATE		
➤ NO MUDFLAP BRACKETS		-25
➤ NO REAR MUDFLAPS		-15
➤ FENDER MOUNTED FRONT MUDFLAPS		
➤ GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
➤ Fuel Tanks		
➤ 80 GALLON/302 LITER ALUMINUM FUEL TANK - RH	110	45
➤ 80 GALLON/302 LITER ALUMINUM FUEL TANK - LH	-10	
➤ 25 INCH DIAMETER FUEL TANK(S)		
➤ PLAIN ALUMINUM FUEL TANK(S) WITH POLISHED STAINLESS STEEL BANDS		
➤ FUEL TANK(S) AFT		
➤ FUEL TANK COMPRESSION BRACE	30	
➤ EQUIFLO INBOARD FUEL SYSTEM		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ Tires		
➤ MICHELIN XFE 425/65R22.5 20 PLY RADIAL FRONT TIRES	172	
➤ MICHELIN XDE M/S 11R22.5 14 PLY RADIAL REAR TIRES		56
➤ MICHELIN XFE 425/65R22.5 20 PLY RADIAL PUSHER/TAG TIRES		172
➤ Hubs		
➤ CONMET PRESET PLUS IRON FRONT HUBS	60	
➤ CONMET PRESET PLUS ALUMINUM REAR HUBS		
➤ CONMET PRESET PLUS IRON PUSHER/TAG HUBS		30
➤ Wheels		
➤ ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC FRONT WHEELS	-8	
➤ ALCOA LVL ONE 88367X 22.5X8.25 10-HUB PILOT ALUMINUM DISC REAR WHEELS		-200
➤ ALCOA LVL ONE 82462X 22.5X12.25 10-HUB PILOT 4.68 INSET 10-HAND ALUMINUM DISC PUSHER/TAG WHEELS		-148
➤ POLISHED FRONT WHEELS; OUTSIDE ONLY		
➤ POLISHED REAR WHEELS; OUTSIDE OF OUTER WHEELS ONLY		
➤ POLISHED PUSHER/TAG WHEELS; OUTSIDE OF OUTER WHEEL ONLY		
➤ Cab Exterior		
➤ 123 INCH BBC STEEL CONVENTIONAL CAB		
➤ WESTERN STAR STAINLESS STEEL CAB SKIRT		
➤ AIR CAB MOUNTS WITH CHECK VALVE		-30
➤ NONREMOVABLE BUGSCREEN MOUNTED BEHIND GRILLE		
➤ 2-3/4 INCH FENDER EXTENSIONS		10
➤ LH AND RH EXTERIOR GRAB HANDLES WITH RUBBER INSERTS AND RH INTERIOR GRAB HANDLE MOUNTED TO A POST		
➤ STAINLESS STEEL RADIATOR SHELL/HOOD BEZEL WITH STYLIZED TILT HOOD HANDLE		
➤ RADIATOR MOUNTED GRILLE		
➤ HEAVY DUTY STEEL CAB FLOOR		
➤ SUPER VISIBILITY HOOD WITH CAB MOUNTED QUARTER FENDERS		
➤ HEAVY DUTY HOOD MOUNTING		
➤ FOUR HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS		12
➤ SINGLE ELECTRIC HORN		
➤ FOUR HORN SHIELDS		
➤ DOORS AND IGNITION KEYED THE SAME (3 KEYS)		
➤ SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ DUAL RECTANGULAR HALOGEN HEADLIGHTS		
➤ LED MARKER LAMPS		
➤ ACCENT LIGHTS ON INTAKE BRACKET AND LOWER EDGE OF CAB	10	
➤ DAYTIME RUNNING LIGHTS WITH ROCKER/TOGGLE MOMENTARY INTERRUPTER SWITCH		
➤ FLUSH MOUNTED STOP/TAIL/BACKUP LIGHTS MOUNTED BELOW REAR MOST CROSSMEMBER		
➤ LED SQUARE CHROME FENDER MOUNTED FRONT TURN SIGNALS		
➤ DUAL MEKRA AERO BRIGHT FINISH HEATED DUAL AXIS 1-PIECE MOTORIZED MIRRORS WITH LIGHTS, LH AND RH REMOTE AND INTEGRAL CONVEX MIRRORS	20	
➤ CAB MOUNTED MIRRORS		
➤ 102 INCH EQUIPMENT WIDTH		
➤ DUAL MEKRA BRIGHT FINISH HEATED CONVEX MIRRORS WITH MANUAL ADJUSTMENT AND DUAL AXIS FOR 1-PIECE PRIMARY MIRRORS		
➤ RH DOWN VIEW MIRROR		
➤ STAINLESS STEEL EXTERIOR SUN VISOR	28	
➤ 17.5X35 INCH TINTED REAR WINDOW		
➤ TINTED DOOR GLASS		
➤ RH AND LH ELECTRIC POWERED WINDOWS		
➤ 2-PIECE TINTED CURVED BONDED WINDSHIELD		
➤ 1.5 GALLON WINDSHIELD WASHER RESERVOIR MOUNTED UNDER CAB WITH REMOTE FILL		
➤ Cab Interior		
➤ SMOKY MOUNTAIN GRAY VINYL PREMIUM INTERIOR		
➤ BLACK HARD TRIM		
➤ BASE LEFT HAND DOOR TRIM		
➤ BASE RIGHT HAND DOOR TRIM		
➤ BLACK MATS WITH DOUBLE INSULATION		
➤ DASH MOUNTED ASH TRAY AND LIGHTER, DRIVER SIDE		
➤ FORWARD ROOF MOUNTED CONSOLE		
➤ PASSENGER SIDE WING DASH MOUNTED GLOVE BOX WITH LOCKING DOOR		
➤ 14"X7.75" DOCUMENT POUCH MOUNTED ON BACK WALL BETWEEN SEATS		
➤ LH AND RH DOOR MAP POCKETS		
➤ COAT HOOK ON RH BACKWALL OF CAB		
➤ BLACK SOFT TOUCH WING DASH WITH DRIVER SIDE COSMETIC UNDER DASH COVER		
➤ STANDARD WIRING		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ 2-1/2 LB. FIRE EXTINGUISHER MOUNTED OUTBOARD OF DRIVER SEAT	5	
➤ HEATER, DEFROSTER AND AIR CONDITIONER WITH COSMETIC COVER		
➤ STANDARD HVAC DUCTING		
➤ STANDARD HEATER PLUMBING		
➤ DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
➤ RADIATOR MOUNTED AIR CONDITIONER CONDENSER		
➤ ADDITIONAL CAB SIDEWALL INSULATION	60	10
➤ CAB DOOR LATCHES WITH MANUAL DOOR LOCKS		
➤ PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER	40	
➤ BASIC HIGH BACK NON SUSPENSION TOOL BOX PASSENGER SEAT	-30	
➤ BLACK SUSPENSION COVER FOR AIR DRIVER SEAT	2	
➤ DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS	4	
➤ ULTRA LEATHER DRIVER SEAT COVER		
➤ ULTRA LEATHER PASSENGER SEAT COVER		
➤ 3 POINT DRIVER AND PASSENGER SEAT BELT RETRACTORS		
➤ ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN		
➤ 2-SPOKE 18 INCH (450MM) BLACK LEATHER WRAPPED STEERING WHEEL		
➤ DRIVER AND PASSENGER INTERIOR SUN VISORS		
➤ Instruments & Controls		
➤ FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH DRIVER INSTRUMENT PANEL		
➤ FIGURED CHERRY WOODGRAIN ULTRA GLOSS FINISH CENTER INSTRUMENT PANEL		
➤ STAR GAUGES WITH BRIGHT BEZELS		
➤ (1) SINGLE BRAKE APPLICATION AIR GAUGE		
➤ 2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES		
➤ INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS		
➤ 97 DB BACKUP ALARM		3
➤ CRUISE CONTROL SWITCHES IN THE CENTER PANEL		
➤ KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY		
➤ WARNING LAMP/LIGHT BAR DISPLAY, NON-DATA LINKED		
➤ HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH		

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
➤ 2 INCH ELECTRIC FUEL GAUGE		
➤ FUEL FILTER RESTRICTION INDICATOR		
➤ ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
➤ ENGINE OIL TEMPERATURE GAUGE		
➤ 2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
➤ DASH MOUNTED PTO CONTROL WITH INDICATOR LIGHT, GUARD AND PIPING	5	
➤ ELECTRIC ENGINE OIL PRESSURE GAUGE		
➤ AM/FM/WB WORLD TUNER RADIO WITH SIRIUS XM, CD PLAYER, BLUETOOTH, IPOD INTERFACE AND USB AND AUXILIARY INPUTS, J1939	10	
➤ ROOF/OVERHEAD CONSOLE MOUNTED RADIO		
➤ (4) RADIO SPEAKERS IN CAB		
➤ COBRA 29 WX ST FACTORY INSTALLED CB RADIO WITH WEATHERBAND	5	
➤ MULTI-BAND AM/FM/WB/CB DUAL MIRROR MOUNTED ANTENNA SYSTEM	4	
➤ INTEROPERABLE SDAR ANTENNA		
➤ ELECTRONIC KPH SPEEDOMETER WITH SECONDARY MPH SCALE, WITH ODOMETER		
➤ ELECTRONIC 3000 RPM TACHOMETER WITH HOUR METER		
➤ VT-HU CONNETIVITY PLATFORM HARDWARE		
➤ 2 YEARS DETROIT CONNECT VIRTUAL TECHNICIAN REMOTE DIAGNOSTICS SERVICE		
➤ IGNITION SWITCH CONTROLLED ENGINE STOP		
➤ TWO ON/OFF ROCKER SWITCHES IN THE DASH WITH INDICATOR LIGHTS AND WIRE ROUTED TO CHASSIS AT BACK OF CAB, LABEL OPT		
➤ BW TRACTOR PROTECTION VALVE		
➤ TRAILER HAND CONTROL BRAKE VALVE		
➤ 2 INCH TURBO AIR PRESSURE GAUGE		
➤ 2 INCH VOLTMETER		
➤ SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
➤ CAB/TRAILER MARKER LIGHT SWITCH WITH SEPARATE HEADLIGHT SWITCH		
➤ TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR		
➤ VSM NON CANCELING TURN SIGNAL SWITCH WITH INTEGRAL HEADLAMP DIMMER WITHOUT BRAKE OVERRIDE		
➤ PACIFIC INSIGHT ELECTRONIC FLASHER		

➤ **Design**

- PAINT: ONE SOLID COLOR

Stock 4900 18 spd White



Description	Weight Front	Weight Rear
> Color		
> CAB COLOR A: HSB905935 WHITE PPG BASE/CLEAR		
> CAB INTERIOR PAINTED SAME AS CAB COLOR		
> BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT		
TOTAL VEHICLE SUMMARY		

Weight Summary			
	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	12887 lbs	9537 lbs	22424 lbs
Total Weight⁺	12887 lbs	9537 lbs	22424 lbs

(+) Weights shown are estimates only.
 If weight is critical, contact Customer Application Engineering.

Stock 4900 18 spd White

