





STANDARD FEATURES

7-wire-harness trailer tow (blunt-cut and labeled)

28-gallon fuel tank capacity (SRW)

40-gallon fuel tank capacity (DRW)

Engine – 6.2L 2-valve V8 FFV (F-350 SRW/DRW)

Engine – 6.8L 3-valve V10 gas (F-450/F-550 XL, XLT)

Engine – 6.7L Power Stroke® V8 Turbo Diesel (B20-capable) (F-450/F-550 LARIAT)

Fail-Safe Engine Cooling System (gas engines)

Front tow hooks (2)

Front twin-coil monobeam suspension (F-350 4x4, F-450 and F-550)

Front Twin-I-Beam with coil spring suspension (F-350 4x2)

Manual transfer case and manual locking hubs (4x4 only)

Mirrors – Manually telescoping trailer tow (XL, XLT)

Stationary elevated idle control (SEIC)¹

SYNC® with MyFord® (XLT, LARIAT)

Tire Pressure Monitoring System (TPMS) (SRW only)

Transmission – TorqShift® 5-speed automatic (6.8L gas)

Transmission – TorqShift Heavy-Duty 6-speed SelectShift® automatic (6.2L FFV and 6.7L diesel)

Upfitter switches (4)

STANDARD SAFETY & SECURITY

AdvanceTrac® with RSC® (Roll Stability Control™) (F-350 SRW)

Airbags – Driver and right-front-passenger front

Airbags – Front-seat side

Airbags – Safety Canopy® System with roll-fold side-curtain airbags

Brakes – Power 4-wheel vented disc with Anti-Lock Brake System (ABS)

Child-safety-seat top tether anchors (Regular Cab front passenger and all rear seating positions on SuperCab and Crew Cab) Engine-only traction control (DRW only)

Front-outboard safety belts with heightadjustable shoulder belts

Passenger airbag deactivation switch (Regular Cab and SuperCab)

SecuriLock® Passive Anti-Theft System (XLT, LARIAT)

Side-intrusion door beams

SOS Post-Crash Alert System™

AVAILABLE FEATURES

28-gallon midship fuel tank

Dual diesel fuel tanks (40-gal. aft-of-axle; 28-gal. midship)

Electronic shift-on-the-fly (ESOF) 4-Wheel-Drive System

Engine – 6.7L Power Stroke V8 Turbo Diesel

Ford Telematics™ powered by Telogis®2

Integrated trailer brake controller with Smart Trailer Tow Connector

Mirrors - PowerScope® trailer tow

Operator Commanded Regeneration (with diesel engine)

Transmission – Live-drive and stationary mode power takeoff (PTO) provision (diesel engine)

Transmission – Power takeoff (PTO) provision (6.8L gas engine)

FLEET EXCLUSIVES

65-mph speed limitation

75-mph speed limitation

Air conditioning delete

Carpet delete

Cruise control

Daytime running lamps

Four-corner strobe

Manual-sliding rear window with privacy glass

Power-adjustable pedals

Radio delete

Tire Pressure Monitoring System delete (F-350 SRW >10,000 lbs. GVWR only)

AVAILABLE PACKAGES³

6.2L CNG/LPG Gaseous Engine Prep Package (F-350) (98F)
6.8L CNG/LPG Gaseous Engine Prep Package (F-450/F-550) (98G)
16,000-lb. GVWR Package (68L)
Heavy-Service Front Suspension Package (67H)
Extra-Heavy-Service Front Suspension Package (67X)
LARIAT Interior Package (96L)
Low Deflection Package (86S)
Payload Downgrade Package (68D)
Payload Upgrade Package (68U)
Payload Plus Upgrade Package (68M)
Power Equipment Group (90L)
Rear View Camera and Prep Kit (76D)

Snow Plow Prep Package (473)	
Trailer Tow Package (531)	
Trailer Tow High-Capacity Package (535)	
XL Appearance Package (96P)	
XL Decor Group (17F)	
XL Value Package (96V)	
XLT Interior Package (96I)	

FLEET EXCLUSIVES

Ambulance Prep Package (47A/47L)
Fire/Rescue Prep Package (47J)

CAPACITIES

		Regular Cab	SuperCab	Crew Cab
Interior volume (cu. ft.)	Total/Rear	65.9/—	113.3/47.4	133.5/67.6
Fuel capacity (gal.)	SRW/DRW	28.0/40.0	28.0/40.0	28.0/40.0

ENGINES

	6.2L 2-valve V8 FFV	6.8L 3-valve V10 Gas	6.7L Power Stroke V8 Turbo Diesel
Battery	12-volt, 650-CCA/72-amp-hr	12-volt, 750-CCA/78-amp-hr	Dual 12-volt, 750-CCA/78-amp-hr
Alternator	157-amp	175-amp	157-amp (single 200-amp or dual 357-amp options)
Horsepower (hp @ rpm)	385 @ 5,500 ⁴	362 @ 4,750	300 @ 2,800
Torque (lbft. @ rpm)	405 @ 4,500 ⁴	457 @ 3,250	660 @ 1,600
Recommended fuel	Regular unleaded or E85	Regular unleaded	Ultra-Low-Sulfur Diesel or B20 (containing 20% or less biodiesel)

MAXIMUM PAYLOAD WEIGHT RATINGS⁵ (lbs.)

	Regular Cab			SuperCab		Crew Cab		
Cab-to-axle (in.)	60	84	108	120	60	84	60	84
Wheelbase (in.)	141	165	189	201	162	186	176	200
Overall length (in.)	226.5	250.5	274.5	286.5	247.5	271.5	261.9	285.9
F-350 SRW 4x2	4,723	_	_	_	4,772	_	4,496	_
F-350 SRW 4x4	4,360	_	_	_	4,323	_	4,057	_
F-350 DRW 4x2	7,872	7,872	_	_	7,619	_	7,361	_
F-350 DRW 4x4	7,541	7,440	_	_	7,126	_	6,932	_
F-450 DRW 4x2	9,945	9,815	9,575	9,486	9,523	9,269	9,325	9,197
F-450 DRW 4x4	9,651	9,495	9,223	9,188	9,194	8,991	8,977	8,846
F-550 DRW 4x2	12,300	12,660	12,471	12,410	12,382	12,214	12,250	12,015
F-550 DRW 4x4	11,973	12,321	12,150	12,049	12,012	11,924	11,800	11,691

EXTERIOR COLORS⁶



INTERIOR COLORS⁶



