

Maintenance Checklist – 911 Carrera/S/4/4S/Turbo/S (991) (2014-16)

* Oil Change Every 10,000 miles (15,000 km) or 1 year. See Below Check Box.

Required Maintenance and Lubrication Service

Note: If the mileage for scheduled maintenance is not reached, maintenance must be performed no later than after 4, 8, 12 years.		
The terms 'check' and 'inspection' include all necessary subsequent work such as adjusting, readjusting, correcting and topping off, but do not include repairing, replacing and reconditioning parts or assemblies.		
Electrics		
Diagnosis system: Read out fault memory; reset maintenance interval		
Windshield wiper/washer system, headlight washer: Check function and nozzle adjustment		
□ Horn: Check operation		
□ Tires: Check tire pressure (TPM)		
Batteries and ventilation hoses: Check condition		
 Electrical equipment as well as indicator and warning lights: Check operation 		
Check actuator travel of brake shoes (911 Turbo/Turbo S only)		
Inside of Vehicle		
Pollen filter: Replace filter element		
Seat belts: check function and condition		
Door locks: check function		
Front Luggage Compartment		
Pollen filter: Replace pre-filter element		
Check front lid lock and safety hook of the front lid for secure seating and function properly		
□ Windshield wiper/washer system, headlight washer: Check fluid level and antifreeze protection level		
Check firewall body drains for debris		
Outside of Vehicle		
Check wiper blades		
Vehicle lighting: Check operation		
All headlights: Check adjustment		
Radiators and air intakes: Visual inspection for exterior debris and blockage		
Check the two Targa center bar drains for debris (911 Targa models only) Under the Vehicle		
Drain engine oil		
❑ Vehicle underside and engine compartment: Visual inspection for leaks (oils and fluids) and abrasion (lines and hoses);		
Underbody panels: visual inspection for completeness, secure installation and damage		
□ Tires: Check condition		
□ Brake system: Visual inspection of the brake pads & brake discs for wear (w/o removing wheels) (Except PCCB)		
□ Vehicles with PCCB: As of MY 2014, PCCB Brake discs must be checked for wear during every service and whenever		
brakes pads are replaced using special tool VAS 6813. Please refer to workshop manual for work procedure.		
Brake hoses and lines: Visual inspection for damage, correct routing and corrosion Check brake fluid level		
Steering gear: Visual inspection of the dust boots for damage		
Tie rod ends: Check play and dust boots		
Rear axle steering: Check bellows, dust boots and play on joints		
Axle shafts/Drive shafts: Visual inspection of the dust boots for leaks & signs of damage/wear		
Lexhaust system: Visual inspection for leaks and damage; check mounting and heat shields		
Engine Compartment		
Air filter: Replace filter elements		
Change oil filter and fill engine oil (Every 10,000 miles/15,000 km, see separate Oil Change Sheet, PNA 000 162 LC)		
Fuel lines and connections: Visual inspection for damage and leaks		
☐ Visual inspection for leaks (oils and fluids)		
Coolant: Check level and antifreeze protection level		
PDCC: Check fluid level		
Check firewall body drains for debris		

Additional Maintenance – Replace Spark Plugs (Labor Operation 03 81 00 ..)

Replace spark plugs: every 40,000 miles / 60,000 km or 4 years (Except Turbo/S)

Replace spark plugs: 911 Turbo/Turbo S every 30,000 miles / 45,000 km or 4 years

Additional Maintenance - Drive Belt Labor operation 03 60 00 ...

Check drive belt at 40,000 miles (60,000 km) or every 4 years

Check drive belt at 100,000 miles (150,000 km) or every 10 years

Check drive belt at 160,000 miles (240,000 km) or every 16 years

Additional Maintenance - Convertible Top (Labor Operation 03 70 00 ..)

Service and maintain convertible top: every 20,000 miles / 30,000 km or 2 years

Additional Maintenance - Targa Roof (Labor Operation 03 71 00 ..)

Service and maintain Targa roof: every 20,000 miles / 30,000 km or 2 years

Additional Maintenance every 60,000 miles / 90,000 km or 6 years (Labor Operation 03 83 00 ...)

- Replace PDCC reservoir
- Replace drive belt

Change all-wheel drive controller oil (4-wheel drive models only)

Additional Maintenance every 80,000 miles / 120,000 km or 4 years (Labor Operation 03 85 00 ...)

Additional Maintenance every 120,000 miles / 180,000 km or 12 years (Labor Operation 03 88 00 ...)

☐ Manual transmission: change oil

- PDK transmission: change oil
- PDK transmission: change clutch oil

All-wheel final drive: change oil (4-wheel drive models only)

Additional Maintenance every 2 years (Labor Operation 03 51 00 ..)

Change brake fluid (use only Original Porsche Brake Fluid)

Tire sealant (check expiration date and replace as necessary)

Inspection Performed - Technician Signature: _

Road Test Check

Remote control, front seats, foot brake and electric parking brake (also operating travel), engine, clutch, steering, transmission, ParkAssist, cruise control, PSM, PASM & Sport switches, sports exhaust system, door mirror fold-in function, heater, air-conditioning system and instruments: Check operation

Oils, fluids: Visual inspection for leaks

Road Test Performed - Technician Signature: ____

Customer Name:	Date://
Mileage (check one) 🗋 Miles 🗋 Kilometers:	
Dealer Name:	Dealer Code:
Repair Order #:	
Technician Name:	
Technician Signature:	