

2010 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145	55/115/175
Familia Oil (Oil Filham alamana ail and ann la a filham			
Engine Oil/Oil Filter – change oil and replace filter	•	•	•
AdBlue Fluid – fill completely with fresh fluid (maximum capacity: 23 liters) and adapt learned values for AdBlue tank under guided fault finding after filling fluid	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only
Cooling System – check level, add if necessary		•	•
Engine On-Board Diagnostics – check fault memory		 A3, A6, S6, A8 only 	A3, A6, S6, A8 only
Engine Compartment – check for leaks		•	•
Battery – check and replace if necessary		•	•
Dust and Pollen Filter – replace		•	•
Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Thereafter, every 40,000 miles or 3 years, whichever occurs first. – replace at 55,000 miles or 6 years, whichever occurs first.		 55K only: except A4, A5 and TTS with 2.0L TFSI engine 	A4, A5 and TTS with 2.0L TFSI engine only
Thereafter, every 60,000 miles or 6 years, whichever occurs first.		with 2.0L TFSI engine	
Power Steering Fluid – check, add if necessary			•
Air Cleaner – clean housing, replace filter element		 55K only: except Audi Q7 4.2L 	75K only: Audi Q7 4.2L only
Ribbed V Belt and Tensioner - check condition and replace if necessary		R8 only	Audi Q7 3.6L, R8 only
Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary. – replace only the V belt for the compressor drive			 75K only: V6 FSI, V6 TFSI (rear be 2.0L TFSI, 5.2L V10 FSI, 4.2L V8 FSI only 75K only: 3.0L TFSI only
Snow Screen for Air Cleaner - clean		 A4, S4, A5, S5 and A6 only 	 A4, S4, A5, S5 and A6 only
Fuel Filter - remove water		Audi Q7 3.0L TDI only	3 7.11, 3-1, 7.5, 35 and A0 only
- replace		A3 2.0L TDI only	Ad: 07.2 OLTDId
- reptace		A3 2.UL IDI only	Audi Q7 3.0L TDI and A3 2.0L TDI only
Diesel Particulate Filter (DPF) – check ash loading according to manufacturer's work procedure, replace* if necessary.	 USA: 125K only: Audi Q7 3.0L TDI, A3 2.0L TDI only Canada: 200,000 km only: Audi Q7 3.0L TDI, A3 2.0L TDI only 		
Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary		except A3, Audi Q5	except A3, Audi Q5
Tires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS)	•		
 - check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS) 		•	•
Tires – rotate, reset TPMS	5K only		
Wiper Blades – check condition and replace if necessary	•	•	•
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	•	•	•
Lights – check all lights, check headlight adjustment		A8 only	A3, A6, S6, A8 only
Lights – check all lights via instrument cluster. Check license plate light from the rear of the vehicle			Audi Q7, A4, S4, Audi Q5, TT, A5, S5, R8 only
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			•
Doors – lubricate doors, check straps and hood latch		A8 only	Except A8
Rear Lid Hinges – lubricate		A8 only	A8 only
Service Reminder Display – reset	•	•	•
Horn – check function		•	•
Brake System – check for damage, leaks, pad thickness, fluid level	0	•	•
Brake Discs – check thickness			•
Exhaust System – check for damage, leaks		•	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends		• A3, A6, S6, A8 only	•
Drive Shaft Boots – check		•	•
Automatic Transmission and Final Drive - check for leaks		•	•
Manual Transmission and Final Drive - check for leaks		•	•
Continuously Variable Transmission (multitronic) – change ATF		-	•
Haldex Clutch - change oil			A3, TT only
•			_
DSG/S Tronic – change oil and replace filter element – change oil			A3, TT onlyS4, S5 only
Underbody – check for damage and leaks		•	•
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock, power accessories and reset driver information display		•	•

Brake Fluid – replace every 2 years regardless of mileage.

pulleys and replace if necessary.

Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A5/S5 Cabriolet only).

*If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (200,000 km), thereafter.

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.