



MAZDA MX-5 MIATA

EVERY 8,000 KM OR 4 MONTHS

- Replace engine oil; Replace oil filter
- Inspect function of all lights
- Inspect brake fluid, clutch fluid, washer fluid and coolant level
- Inspect all tires inflation and wear
- Lubricate all locks and hinges
- Rotate tires (priced separately)
- Inspect air filter

EVERY 24,000 KM OR 12 MONTHS

Includes 8,000 km service, plus:

 Inspect and clean brake discs and pads, front and rear

EVERY 48,000 KM OR 24 MONTHS

Includes 24,000 km service, plus:

- Inspect fuel lines and hoses
- Inspect brake lines, hoses and connections
- Inspect steering operation and linkage
- Inspect front and rear suspension components, ball joints and wheel bearing axial play
- Replace manual transmission oil (if M/T equipped)
- Inspect driveshaft dust boots
- Tighten bolts and nuts on chassis and body

EVERY 56,000 KM OR 28 MONTHS

Includes 8,000 km service, plus:

- Inspect drive belts
- Replace air cleaner filter

EVERY 72,000 KM OR 60 MONTHS

Includes 24,000 km service, plus:

Inspect exhaust system and heat shields

EVERY 96,000 KM OR 48 MONTHS

Includes 48,000 km service, plus:

• Inspect emission hoses and tubes

EVERY 120,000 KM

Includes 24,000 km service, plus:

• Replace spark plugs*

EVERY 192,000 KM OR 10 YEARS

• Replace coolant, after that every 96,000 km or 5 years

ADDITIONAL OPERATIONS

- Inspect flat tire repair kit (if installed) annually
- If Rear Differential has been submerged in water, replace oil

At each visit, we'll provide you with an exclusive Vehicle Inspection Report,

which shows you the overall condition of your Mazda.

CLICK HERE FOR AN ENLARGED VERSION

COTONES NAME:

COTONE

Scheduled services may vary by year of vehicle. Please consult your Service Advisor for the specific maintenance intervals pertaining to your vehicle. 24,000 km and 56,000 km services includes service performed at 8,000 km interval. 48,000 km service includes service performed at 8,000 km service includes service performed at 8,000, 24,000 and 48,000 km intervals. Use of FL-22 is recommended when replacing engine coolant. Using engine coolant other than FL-22 may cause serious damage to the engine and cooling system.

TO LEARN MORE, CLICK ON LOGO





Mazda FULL CIRCLE SERVICE

Your Mazda Dealer will provide you with a completed service checklist on every maintenance visit. In addition, your Mazda will be road tested after any servicing relating to brakes, steering or driving performance, to help verify safe functioning. Information listed in this document is accurate at time of publication and is subject to change without notice. Ask your Mazda Dealer for more detailed information. This inspection list/schedule is intended as a guide only and should not be relied upon to ensure vehicle safety. See your Mazda dealer for full details, maintenance and inspection.

* Maintenance intervals may vary based on driving conditions. Please refer to owners manual.



VEHICLE HEALTH < CHECK



| CUSTOMER NAME: | | R.O. #: | SERVICE ADVISOR: | |
|---|----------------------------------|--|--|--|
| VIN (LAST 6 DIGITS): | LICENCE PLATE #: _ | ODO | METER: | _ DATE: |
| ⋘ GOOD - CHECKED OK | FAIR - REQUIRES FUTURE ATTENTION | ▼ REPLACE - REQUIRES | IMMEDIATE ATTENTION CHE | CKED FOR OUTSTANDING RECALLS |
| PERIMETER INSPECTION FRONT Lights/lamps Windshield Washer system Wipers/arms Body damage Horn operation | | REAR Lights/lamps Washer system Wipers/arms Body damage | NEXT MAINTENAN NEXT MAINTENANCE SERVICE NEXT APPOINTMENT | DEALER CODE DATE (MM/DD/YY) TIME |
| VISUAL INSPECTION UNDER HOOD Fluid levels (brakes, stee clutch, window washer, coo manual/automatic transmit Drive belt(s) Air filter Radiator, hoses/clamp and coolant condition C Heater hoses/clamps Air conditioning hoses Battery/cables/clamp | lant and sision) | Suspension components Shocks & Struts Exhaust system CV drive axle boots (if equipped) CHECK FOR LEAKS Engine oil Transmission | COMMENTS & RECOMM | ENDATIONS: |
| BRAKE INSPECTION Lining/pad Rotor Caliper Lines/hose Lining/pad Caliper Lines/hose Lining/pad Lines/hose Lines/hose | LF RF | | MEASURE FRONT / REAR B LF 50%+ 20%-50% 0%-20% LR 50%+ 20%-50% 0%-20% Measurements Not Taken | RAKE LININGS RF 50%+ 20%-50% 0%-20% RR 50%+ 20%-50% 0%-20% Obeclined Brake Inspection |
| TIRE INSPECTION WINTER TIRES Tread Wear 32 ^{nds} Tread Wear 32 ^{nds} LF | RR LR RECOMMENDED: | SPARE PSI LL SEASON TIRES Tread Wear 32nds Tread Wear 32nds Tread Wear 32nds ALIGNMENT REPLACEMENT BALANCE | 20% - 50 | |